

XPS-092T1

8 port 10/100 PoE + 1 port 10/100TX Uplink Unmanaged Switch



- 8 Port 10/100 PoE
- 1 Port 10/100 Megabit Uplink
- Total PoE Budget: 110W
- IEEE802.3x
- Multi-function Switch
- Long Distance PoE (250m)
- Enable and Disable VLAN

Technical Specs.

Model No	XPS-092T1
Port Capacity	9-Port Megabit PoE Switch
Port Types	8 port 10/100Base-TX RJ45 copper ports (PoE) + 1 port 10/100 RJ45 copper port

Performance

Switching Capacity	1.8 Gbps (non-blocking)
Forwarding Rate	1.34 Mpps
MAC Table	2K

Features

Switch Architecture, Store-and-Forward	Auto MDI/MDIX
IEEE 802.3	Auto Negotiation
IEEE 802.3i	IEEE 802.3af
IEEE 802.3u	IEEE 802.3x, Flow Control

Switch Mode Features

Mode 1	Standard Switch Mode
Mode 2	Enable Long Distance Transmission for all ports (8 port/10 Mbps/250m)
Mode 3	Enable VLAN for 10/100M ports (1-8 ports)

PoE

Standard	IEEE802.3af
Total PoE Budget	110 W
Max. PoE Power for each port	15.4 W

Environment

DC Power Input	47-55V
Total Power Consumption	121 W
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Operating Humidity	10% - 90%, non-condensing

Mechanical

Dimension	195 x 110 x 35 mm
Weight	0.493 kg
Installation	Free-standing, wall-mounted

Standards and Protocols

CE Marks, commercial	EN 55022 (CISPR 22), Class B	VCCI Class B
EN 55022 (CISPR 22), Class B	CE/LVD EN60950, RoHS	ISO 9001

Ordering Information

XPS-092T1	8 port 10/100 PoE + 1 port 10/100TX Uplink Unmanaged Switch
------------------	---