

XPS-1220-14F

12 port 100/1000 SFP + 2 port 10/100/1000T L2+ Managed Fiber Switch



- 12 Port 100/1000 SFP
- 2 Port 1000BaseT
- L2+ Features
- IEEE802.3x
- IEEE802.3z/ab

Technical Specs.

Model No	XPS-1220-14F
Port Capacity	14 Port Gigabit Managed Switch
Port Types	12 x 100/1000 SFP ports + 2x 10/100/1000Base-T RJ45 copper ports + 1 RJ45 console port

Performance

Switching Capacity	28 Gbps, wire speed, (non-blocking)
Forwarding Rate	20,8 Mpps
MAC Table	8K
Jumbo Frames	9.6KB
Memory	6M
Auto-negotiation	•
Auto MDI/MDIX	•
Store-and-Forward	•

Layer 2+ Features

Spanning Tree Protocol (STP)	IEEE802.1d Spanning Tree Protocol IEEE802.1w Rapid Spanning Tree Protocol IEEE802.1s Multiple Spanning Tree Protocol Loop Back Detection
IGMP Snooping	IGMP v1/v2
VLANs	Support up to 4K VLANs Port-based VLAN 802.1Q tag-based VLAN
Link Aggregation (TRUNK)	IEEE 802.3ad LACP
Ethernet Ring Protection Switching	G.8032 ERPS
Flow Control	IEEE802.3x
Private VLAN	•
Layer 3 Static Routing	•
Q in Q	•

Security Features

<p>Broadcast, multicast , unicast storm control Secure Sockets Layer (SSL), Web security DHCP Snooping ARP Inspection IP Source Guard AAA, RADIUS and TACACS+</p>	<p>Secure Shell (SSH), Telnet security, supports SSH v1 and v2 ACL, VLAN ID or IP address, MAC Based, Protocol based, Port Based, TCP/ UDP Ethernet type, IGMP, TCP flag Port Security</p>
--	---

Management

Web/SSL	SNMP	Firmware upgrade,
Port Mirroring	DHCP Client	(HTTP/HTTPs and TFTP)
Port Isolation	Web GUI Interface	LLDP
Telnet/SSH	Cable Diagnostics	SNTP
Ping	CPU Load	TFTP
HTTP/HTTPs	Dual Image	Syslog
Timezone		

IPv6

IPv6 MLD snooping	IPv4/IPv6 Management
-------------------	----------------------

Quality of Service

CoS	8 queues per port TCP/ UDP Strict priority Weighted Round Robin (WRR)
Rate Limiting	Ingress/Egress Rate control
Traffic classification	IEEE802.1p DSCP / IP precedence
ToS	•
First Come First Served	•
Head of Line	•
Best Effort Service	•

Environment

Input Power	AC100-240V, 50-60Hz
Total Power Consumption	30 W
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Operating Humidity	10% - 90%, non-condensing



Mechanical

Dimension	270 x 181 x 44.5 mm
Weight	1.49 kg
Installation	Free-standing, wall-mounted , 19' Rack mounted

Standards

CE mark, commercial	FCC Part 15 Class B
VCCI Class B	ISO 9001
EN55022 (CISPR 22), Class B	CE/LVD EN60950, RoHS

Ordering Information

XPS-1220-14F 12 port 100/1000 SFP + 2 port 10/100/1000T L2+ Managed Fiber Switch

Modules

XPS-21LX XPS Dual Core LX SM 10Km SFP Module -10/50°C
XPS-21SX XPS Dual Core SX MM SFP Module -10/50°C

*more module ranges are available upon request.