

XPS-I550FPB

1 port 10/100/1000T PoE + 1 port 100/1000SFP Industrial Converter



- 10/100/1000BaseT
- 100/1000Base SFP
- Auto MDI/MDIX
- Auto-Negotiation
- 802.3af/at/bt PoE
- IEEE802.3x
- LFPT
- Watchdog for Fiber Port
- Watchdog for PD Devices
- 250mt PoE Reach

Technical Specs.

Model No	XPS-I550FPB
Port Types	1xRJ45 copper PoE ports +1 port 100/000Base SFP

Performance

Switching Capacity	4 Gbps
Forwarding Rate	3.00 Mpps

Features

IEEE 802.3	Auto-Negotiation
IEEE 802.3i	Store and Forward
IEEE 802.3u	Link Fault Pass Through
IEEE 802.3af/at/bt PoE	Watchdog for Fiber Port
Supports 250mt PoE	Watchdog for PD Devices

Environment

DC Power Input	12-57V (PoE 48-57V)
Power Consumption	95W
Operating/Storage Temperature	-40 - 75 °C / -50 - 85 °C
Operating Humidity	5% - 95%, non-condensing

Mechanical

Dimension	100 x 86 x 36 mm
Weight	0.39 kg
Installation	IP40 rating, DIN35 Rail Type

Standards and Protocols

CE mark, commercial	EN61000-3-2	EN61000-4-6
VCCI Class B	EN61000-3-3	EN61000-4-8
FCC Part 15 Class B	EN61000-4-2	IEC60068-2-6
CE/LVD	EN61000-4-3	EN61000-6-2
ISO 9001	EN61000-4-4	EN61000-6-4
EN 55022 (CISPR 22), Class B	EN61000-4-5	IEC60068-2-27 Ea

Ordering Information

XPS-I550FPB	1 port 10/100/1000T PoE + 1 port 100/1000Base SFP Industrial Converter
--------------------	--

Modules

XPS-I21LX	XPS Industrial Dual Core LX SM 10Km SFP Module -40/75°C
XPS-I21SX	XPS Industrial Dual Core SX MM SFP Module -40/75°C

*more module ranges are available upon request.