

XPS-I552C

1 port 10/100/1000T + 1 port 1000BaseLX Duplex SC 20Km Industrial Converter



- 10/100/1000BaseT
- 1000BaseLX 20Km
- Auto MDI/MDIX
- Auto-Negotiation
- IEEE802.3x
- LFPT

Technical Specs.

Model No	XPS-I552C
Port Types	1x RJ45 copper ports + 1 1000BaseLX Duplex SC 20Km

Performance

Switching Capacity	4 Gbps
Forwarding Rate	3.00 Mpps

Features

IEEE 802.3	Auto-Negotiation
IEEE 802.3i	Store and Forward
IEEE 802.3u	Link Fault Pass Through

Environment

DC Power Input	12-48V
Power Consumption	5W
Operating/Storage Temperature	-40 - 75 °C / -50 - 85 °C
Operating Humidity	5% - 95%, non-condensing

Mechanical

Dimension	93 x 87 x 33 mm
Weight	0.35 kg
Installation	IP40 rating, DIN35 Rail Type

Standards and Protocols

CE mark, commercial	EN61000-3-2	EN61000-4-6
VCCI Class B	EN61000-3-3	EN61000-4-8
FCC Part 15 Class B	EN61000-4-2	IEC60068-2-6
CE/LVD EN60950	EN61000-4-3	EN61000-6-2
ISO 9001	EN61000-4-4	EN61000-6-4
EN 55022 (CISPR 22), Class B	EN61000-4-5	IEC60068-2-27 Ea

Ordering Information

XPS-I552C	1 port 10/100/1000T + 1 port 1000BaseLX Duplex SC 20Km Industrial Converter
------------------	---

Modules

XPS-I21LX	XPS Industrial Dual Core LX SM 10Km SFP Module -40/75°C
XPS-I21SX	XPS Industrial Dual Core SX MM SFP Module -40/75°C

*more module ranges are available upon request.